FLORIDA POWER AND LIGHT CO. EASEMENT
SOUTH LINE OF LOT 10 O.R.B. 2685, PAGE 2410

LOT 59

439.35' (D

LOT 57

439.37' (

R=5206.92'

CH=N35°59'24"W

TOTAL

LOT 10

WOOD FENCE CHAIN LINE FENCE 1.4' NORTH 1.5' NORTH

LOT 55B

"HOPSON'S SUBDIVISION"

530.62' (D) & (M)


6.357 ACRES +/-

D=5°50'29"

## SURVEYORS NOTES:

- 1. THE BEARING BASIS FOR THIS SURVEY IS THE SOUTH LINE OF LOT 10, HOPSON'S SUBDIVISION WHICH BEARS S89°02'54"W, PER DESCRIPTION PROVIDED, AND AS SHOWN
- 2. THE BUILDINGS ON THE PARCEL DESCRIBED HEREIN ARE IN FLOOD ZONE "X" AS PER THE NATIONAL FLOOD INSURANCE PROGRAM. FLOOD INSURANCE RATE MAP
- #12009C 0540 E DATED 4-3-89.
  3. THE LEGAL DESCRIPTION AND EASEMENTS SHOWN HEREON ARE AS FURNISHED BY OLD REPUBLIC NATIONAL TITLE INSURANCE COMPANY, COMMITMENT NO.
- 19-2010-978, DATED: 9-21-10, AND HAS NOT BEEN ABSTRACTED BY THE UNDERSIGNED FOR EASEMENTS, RIGHTS OF WAY OR RESERVATIONS OF RECORD.
- 4. PRIMARY BENCHMARK IS DESIGNATED "W401" BY NGS AND IS A STAINLESS STEEL ROD IN CASING EAST OF THE "RIVERS EDGE" SIGN ON THE WEST SIDE OF U.S. HIGHWAY NO. 1 AND ON SUBJECT PROPERTY, ELEVATION = 24.97 FEET, NGVD 1929.
- 5. BELOW GROUND IMPROVEMENTS MAY NOT BE DEPICTED ON THIS MAP OF SURVEY.
- 6. THE SAFE UPLAND LINE HAS BEEN SUGGESTED BY THE DEPARTMENT OF NATURAL RESOURCES AS BEING AT OR ABOVE THE MEAN/ORDINARY HIGH WATER LINE. THIS
- LINE IS NOT A BOUNDARY, AS THE TRUE MEAN/ORDINARY HIGH WATER LINE HAS NOT BEEN DETERMINED, PER THIS SURVEY.

  7. ACREAGE SHOWN IS COMPUTED TO THE EXISTING SAFE UPLAND LINE OF 1.1' NGVD 1929, AS LOCATED ON 10-27-10.
- 8. THE FLORIDA DEPARTMENT OF NATURAL RESOURCES IS WAITING FOR THE NATIONAL OCEAN SURVEY (NOS) TO COMPLETE THEIR ANALYSIS OF DATA CONCERNING THE INDIAN AND BANANA RIVERS, AND WILL NOT AT THIS TIME RECOMMEND AN APPROVED METHOD OF DETERMINING THE BOUNDARY LINE ALONG THE INDIAN RIVER. (MEMO
- INDIAN AND BANANA RIVERS, AND WILL NOT AT THIS TIME RECOMMEND AN APPROVED METHOD OF DETERMINING THE BOUNDARY LINE ALONG THE INDIAN RIVER.
  FROM THE FDEP, DATED 3-09-05, IS ON FILE IN OUR OFFICE).
- 9. BUILDING OVERHANGS ARE NOT NECESSARILY SHOWN.
  10. THE DESCRIPTION PROVIDED AND SHOWN HEREON CALLS "ALONG THE SOUTH LINE OF SAID LOT 6", WHICH IS INCORRECT, IT SHOULD READ "ALONG THE NORTH LINE



2 STORY BRICK

SCHOOL BUILDING

F.F.E. = 22.32'

BROKEN ASPHALT TRAIL

CENTERLINE OF 10'
FLORIDA POWER AND LIGHT
O.R.B. 2707, PAGE 2676

SLIDES & JUNGLE JIM

> FILLED IN POOL

BRICK PUMP BUILDING

S 89°02'54" W

BEARING BASIS

LOT 61

LOT 63

TROPICAL TRAILOR TOWN

To: Florida Institute of Technology, Inc., Old Republic National Title Insurance Company and Thomas R. Allen, P.A.:

This is to certify that this map and the survey on which it is based were made in accordance with the "Minimum Standard Detail Requirements for ALTA/ACSM Land Title Surveys," jointly established and adopted by ALTA and NSPS in 2005. Pursuant to the Accuracy Standards as adopted by ALTA and NSPS and in effect on the date of this certification, undersigned further certifies that in my professional opinion, as a land surveyor registered in the State of Florida, the Relative Positional Accuracy of this survey does not exceed that which is specified therein.

## DESCRIPTION (AS PROVIDED)


BEING THAT PART OF LOT 6 OF HOPSON'S SUBDIVISION OF THAT PORTION OF SECTION 24, TOWNSHIP 28 SOUTH, RANGE 37 EAST, LYING SOUTH AND WEST OF LOT 10 OF THE SAME SUBDIVISION AND EXTENDING WESTWARD TO TURKEY CREEK AND DEER RUN, AS PER PLAT RECORDED IN PLAT BOOK 1, PAGE 62, AND DEED RECORDED IN DEED BOOK V, PAGE 697, PUBLIC RECORDS OF BREVARD COUNTY, FLORIDA,

LESS AND EXCEPT TROPICAL TRAILER TOWN, ACCORDING TO THE PLAT THEREOF AS RECORDED IN PLAT BOOK 12, PAGE 83, PUBLIC RECORDS OF BREVARD COUNTY, FLORIDA.

ALSO, ALL OF THAT PART OF LOT 10, OF HOPSON'S SUBDIVISION OF THAT PART OF SECTION 24, TOWNSHIP 28 SOUTH, RANGE 37 EAST, LYING SOUTH AND EAST OF TURKEY CREEK, ACCORDING TO PLAT RECORDED IN PLAT BOOK 1, PAGE 62, PUBLIC RECORDS OF BREVARD COUNTY, FLORIDA, LYING WEST OF U.S. HIGHWAY NO. 1.

## ALSO DESCRIBED AS:

PART OF LOTS 6 AND 10 OF HOPSON'S SUBDIVISION, AS RECORDED IN PLAT BOOK 1, PAGE 62, OF THE PUBLIC RECORDS OF BREVARD COUNTY, FLORIDA, LYING WEST OF U.S. HIGHWAY NO. 1, BEING MORE PARTICULARLY DESCRIBED AS FOLLOWS, BEGINNING AT THE NORTHEAST CORNER OF LOT 53, TROPICAL TRAILER TOWN, AS RECORDED IN PLAT BOOK 12, PAGE 83, OF THE PUBLIC RECORDS OF BREVARD COUNTY, FLORIDA, THENCE S89°02'54"W, ALONG THE NORTH LINE OF SAID PLAT OF TROPICAL TRAILER TOWN AND THE SOUTH LINE OF SAID LOT 10 OF HOPSON'S SUBDIVISION, A DISTANCE OF 439.35 FEET; THENCE S89°27'54"W, ALONG THE SOUTH LINE OF SAID LOT 6, A DISTANCE OF 113 FEET, MORE OR LESS TO THE EASTERLY ORDINARY HIGH WATER LINE OF DEER RUN CANAL; THENCE NORTHERLY ALONG SAID EASTERLY ORDINARY HIGH WATER LINE OF DEER RUN CANAL, A DISTANCE OF 505 FEET, MORE OR LESS, THENCE N19°01'50"E, A DISTANCE OF 4 FEET, MORE OR LESS, TO THE NORTH LINE OF AFORESAID LOT 6; THENCE N88°52'29"E ALONG THE NORTH LINE OF SAID LOTS 6 AND 10 A DISTANCE OF 438 FEET, MORE OR LESS TO A POINT ON THE WESTERLY RIGHT OF WAY LINE OF U.S. HIGHWAY NO. 1 (S.R. NO. 5); THENCE SOUTHERLY ALONG SAID WESTERLY RIGHT OF WAY LINE AND ALONG A CURVE BEING CONCAVE SOUTHWESTERLY, HAVING A RADIUS OF 5206.92 FEET, A CENTRAL ANGLE OF 5°50'29" AND A CHORD BEARING OF S35°59'24"E, AN ARC DISTANCE OF 530.85 FEET, THENCE S56°55'51"W A DISTANCE OF 10.00 FEET TO A POINT ON A CURVE BEING CONCAVE SOUTHWESTERLY, HAVING A RADIUS OF 5196.92 FEET, A CENTRAL ANGLE OF 0°42'39" AND A CHORD BEARING OF S32°42'50"E; THENCE SOUTHEASTERLY ALONG SAID CURVE AN ARC DISTANCE OF 64.48 FEET TO A POINT ON THE SOUTH LINE OF SAID LOT 10; THENCE S89°02'54"W, A DISTANCE OF 151.20 FEET TO THE POINT OF BEGINNING.



L	JTILITY	LEGEND
	= = = = = =	BELL SOUTH MANHOLE/RISER CABLE TV RISER CLEAN OUT DRAINAGE CURB INLET DRAINAGE MANHOLE ELECTRICAL BOX FIRE HYDRANT FLOOD LIGHT
G.T.I.	_	GAS VALVE GRATE TOP INLET
6.1.1.		GUY ANCHOR
Ę	_	
رقر		HANDICAPPED SIGN/SPACE
O	=	IRRIGATION CONTROL VALVE
$\Rightarrow$	=	LIGHT IN GROUND
₽	=	PHONE RISER
Ш	-	POWER POLE, CONCRETE
þ	=	POWER POLE, WOOD
S	=	SEWER MANHOLE
0	=	SIGN POLE
0 0	=	
25	=	SPEED LIMIT SIGN
STOP	=	STOP SIGN
T	=	TRAFFIC BOX
R	=	TURN ARROW, RIGHT
	=	TURN ARROW, LEFT
W.M.	=	WATER METER
<b>%</b> S⁄	=	WATER STUB-OUT
wv	_	WATER VALVE
$\bowtie$	_	WATER VALVE

L1	26.52	N08°49′05″W
L2	83.13	N17°00′46″W
L3	62.56	N16°25′35″W
L4	91.98	N13°17′18″W
L5	50.11	N17°57′51″W
L6	67.38	N20°20′40″W
L7	36.36	N05°53′01″W
L8	28.55	N13°54′16″E
L9	40.85	N23°47′50″E
L10	22.74	N38°03′47″E
L11	6.35	N62°24′18″E
L12	15.78	S69°43′07″E
L13	22.82	S66°01′54″E
L14	26.21	\$40°56′59″E
L15	22.32	S11°31′45″W
L16	38.74	\$40°49′36″E
L17	35.75	\$57°33′09″E
L18	40.79	\$69°02′46″E
L19	53.17	N78°02′15″E
L20	36.26	N68°19′42″E
L21	32.40	N56°50′52″E
L22	27.22	N13°12′34″E
L23	23.69	N12°01′08″W
L24	40.29	N31°21′00″W

LENGTH |

BEARING

HORIZON SURVEYORS	
OF CENTRAL FLORIDA, INC. LB 630	60
390 POINCIANA DR., MELBOURNE, FL 32935	
E-MAIL: HORIZONSURVEYORS@CFL.RR.COM	

PHONE: (321) 254-8133 FAX: (321) 254-8193

SCALE 1" = 40'	REVISION TABLE			
DATE 11-09-10	DATE	DESCRIPTION	BY	APVD
FIELD BOOK 197				
& PAGE 10				
FIELD DATE				
10-26-10				

FD. 3/4" I.R.

LOT 64

|S 89°27′54" W | 113' +/-

I HEREBY CERTIFY THAT THE PROPERTY HEREON WAS SURVEYED UNDER MY DIRECT SUPERVISION AND THAT THIS MAP OF SURVEY IS ACCURATE AND CORRECT. I FURTHER CERTIFY THAT THIS SURVEY MEETS OR EXCEEDS THE MINIMUM TECHNICAL STANDARDS SET FORTH BY THE FLORIDA BOARD OF PROFESSIONAL SURVEYORS IN CHAPTER 5J-17, FLORIDA ADMINISTRATIVE CODE, PURSUANT TO SECTION 472.027, FLORIDA STATUTES.

— FD. <del>5/8"</del> I.R. "LB 1812" R=5196.92' D=0\*42'39" CH=N32\*42'50"W 64.47' (D)

> R=5196.92' D=0<u>'42'27</u>"

> > 8 89°02'54" W 151.20' (D) & (M)

GRAPHIC SCALE

( IN FEET )
1 inch = 40 ft.

TAX PARCEL #

ROBERT R. DOERRER, JR.

PROFESSIONAL LAND SURVEYOR #3982

NOTE: THIS SKETCH IS NOT
VALID UNLESS IT BEARS
A SIGNATURE AND AN
EMBOSSED SURVEYOR'S
SEAL.

SURVEY FOR:

F.I.T. - PB

DRAWING NUMBER:

6084